

## **350-625 KVA**



### General Feature

The canopy is manufactured with a steel outer skin, and is lined with fire proof, acoustic material. Attenuators are placed on the hot air outlet and cooling air inlet and exhaust silencers of the residential type are mounted either on top of, or inside the enclosure, exhausting to atmosphere.

### **Robust/Highly Corrosion Resistant Construction**

- Body made from steel components treated with polyester powder coating
- Black finish stainless steel locks and hinges
- Zinc plated or stainless steel fasteners

### **Excellent Access for operation and Maintenance**

- Two doors on the side, convenient to install, watch, operation or maintenance On door or other appropriate place set watching window to watch the panel of controller
- Lube oil and cooling water drains piped to exterior of the enclosure
- Simply, convenient operation, not need building generator room, using at the open air
- Setting silencer, on reaching destination, generator can work at any moment.
- Lifting points on base frame

### **Security and Safety**

favorable aeration system and radiation-proof frame

high-powered shock absorption system , assure generator running reposefully

Exhaust silencing system totally enclosed for operator safety

Fuel fill and battery can only be reached via lockable access doors

Emergency stop push button (red) mounted on enclosure exterior

### **Lower noise and lower exhaust**

Setting exhaust, container vent-pipe is circumfluence pipeline, ensure input or output air smoothly

Setting silencer, adopt late-model professional anechoic material, running quiet, noise under 75 db, no influence daily live

### Dimensions & weight

ENGINE SIZE	LENGTH	WIDTH	HEIGH	WEIGHT
350	4100	1400	2470	4555
400	4100	1400	2470	4585
450	4500	1500	2470	5345
500	4620	1500	2500	5395
625	5300	2100	2800	5432